

HANKOOK TIRE  
*Original Equipment*





## Original Equipment supplier for global car manufacturers

This catalogue introduces Hankook tires used as Original Equipment by global automobile manufacturers and explains Hankook Tire's warranty service. It was designed to serve as a guideline to automobile and tire wholesalers as well as their retailers.

Hankook Tire endeavors to produce high quality tires and to provide an immediate solution to consumer complaints referring to Hankook's products. Hankook Tire regards accurate determination of the cause of consumer complaints combined with fast, consumer oriented service as the most critical features of a successful after-sales service. With this catalogue Hankook aims to provide its wholesalers and retailers with the necessary guidance and to meet its service objective.

## Contents

- 04 TEST RESULT
- 06 VOLKSWAGEN, AUDI
- 08 FORD(EU)
- 10 OPEL, LAND ROVER
- 12 HYUNDAI
- 16 KIA
- 20 CHEVROLET(GMDAT)
- 22 SSANGYONG, RENAULT/SAMSUNG
- 24 MITSUBISHI, MINI
- 26 DAIHATSU
- 28 EUROPE HANKOOK OFFICE NETWORK
- 29 HANKOOK LIMITED WARRANTY





# ALWAYS RIDING AT THE TOP

## The latest test results:

"The S1 evo has a high and well-balanced performance potential with safe handling abilities and short braking distance on wet as well as on dry roads. Since it passes all disciplines without problems it can take the winner's lap.  
Auto BILD sportscars (Volume 4/2007)

### Auto-Bild-sportscars-Verdict: Exemplary



## VENTUS S1 evo



"The Korean takes the lead in the entire competition during braking. At similar high level, the Korean convinces with the best braking values on wet and dry roads. Overall, it belongs to the best."

### Auto-Bild-Verdict: Winner of the test



## VENTUS V12 evo



"The positive surprise: The new Ventus Prime literally digs into the asphalt better than any of the renowned brands. Very good handling abilities and excellent braking performance on wet and dry road, good with aquaplaning. The sensation is perfect: In the overall rating, the Hankook takes first place with a good distance in front of a median field of quite recommendable tires!" Auto motor und sport (Volume 7/2008)

### Auto-motor-und-sport-Verdict: Winner of the test



## VENTUS PRIME



Excellent ride comfort for every condition. Particularly, it has dynamic handling at snowy roads and short braking distance for both wet and dry road surfaces. (Volume 9/2008)

### Auto-Bild-Verdict: Very Recommendable




## OPTIMO 4S




## KINERGY ECO

- State-of-the-art passenger car tyre concept already accommodates future standards
- Fuel efficiency through significantly lower rolling resistance
- Anti-vibration technology delivers comfort and efficiency



## OPTIMO K715

- Newly developed Top-Performance-Tires
- Optimized aquaplaning safety and maximum grip on wet
- Convinces with its high driving comfort and low noise running
- Maximized mileage provides for excellent efficiency
- Optimized handling with TCT-Technology



## OPTIMO K415

- Newly developed Top-Performance-Tire with excellent dry and wet abilities
- The optimized tread design guarantees maximum aquaplaning safety
- Maximized driving comfort and low take-off noise
- Optimized handling with TCT-Technology
- High mileage combined with maximum safety reserves



## OPTIMO K406

- The perfect choice for driver and environment
- Optimum handling and driving comfort through newly developed silica-tread mixture and TCT-Technology
- Very good traction on wet roads
- Low rolling resistance and fuel consumption



## Dynapro HP

- On-Road-High performance tires for powerful off-road and SUV-vehicles
- Dynamic tread guarantees sportiness and a maximum in security
- High driving comfort and minimized noise



## RADIAL RA08

- Economic transporter tires from 12 to 16 inches for all wheel positions
- High mileage and excellent in efficiency
- Very good traction values on dry and wet roads




\*Only in the UHP-range.

# VOLKSWAGEN



HANKOOK TIRES  
FITTED ON  
VOLKSWAGEN CARS.



Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
 CADDY		195/65R15 91T	K425	633	207	8.0
 CADDY MAXI		205/55R16 94H XL	K415	635	209	7.8
 NEW POLO		185/60/R15 84T	K415	605	197	8.7
		185/60/R15 88H XL	K415	605	197	8.7
		195/55/R15 88H	K415	606	197	8.7
 GOLF VI		195/65/R15 91T	K415	638	212	8.7
		195/65/R15 91H	K415	638	212	8.7
		205/55/R16 91V	K115	630	227	8.2
		205/55/R16 91V XL	H730	636	224	8.2
 GOLF, EOS, ALTEA (SEAT)		T125/70R16 96M	S300	582	126	3.6
 TIGUAN		215/65R16 98H	RA23	689	224	8.1
 T5		215/65/R16C 106/104T 6P	RA28	686	224	10.0
		205/65R16C107/105T8P	RA28	672	212	10.0
		255/45R18W 103W 4P	K115	686	263	8.8



# AUDI



HANKOOK TIRES  
FITTED ON  
AUDI CARS.

Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
 A3		225/45ZR17 91W	K107	638	225	8.4
		225/45ZR17 94Y XL	K107	638	225	8.4
		T125/70R16 91M	S300	582	126	3.6
 A4		T125/70R19 100M	S300	658	125	3.6









OBS : -O/D (Overall Diameter) -S/W (Section Width) -O.S.D (Original Skid Depth)



# FORD(EU)



Car Model    Model Type    Tire Size    Tire Pattern    O.D (mm)    S.W (mm)    O.S.D (mm)

	TRANSIT	185/75R16 104/102R 8PR	RA08	686	183	10.9
		215/75R16 113/111R 8PR	RA08	728	217	11.3
		195/70R15 100/98R 6PR	RA08	655	196	10.4
		195/70R15 104/102R 8PR	RA08	655	196	10.4
		205/65R16 107/105T 8PR	RA14	672	200	9.2
		215/75R16 116/114R 10PR	RA08	728	210	11.6
		195/75R16 107/105R 8PR	RA08	698	190	10.2
	C-MAX / FOCUS	195/65R15 91V	K105	635	199	8.1
		205/55R16 91V	K107	631	215	8.0
		T125/90R16 98M	S300	631	125	3.5
	FUSION	195/60R15 88T	K406	615	201	8.2
	NEW FIESTA	175/65R14 82T	K715	581	175	7.6
		175/65R14 82H	K715	581	175	7.6
		195/50R15 82H	K107	577	201	8.0
		195/50R15 82V	K107	577	201	8.0
		195/45R16 84V	K107	580	193	7.8
	MONDEO	215/55R16 93V	K107	640	217	8.1
		215/55R16 93H	K107	640	217	8.1
		205/55R16 91V	K107	631	215	8.0
		205/55R16 91H	K107	631	215	8.0
		T125/90R16 98M	S300	631	125	3.5
	KUGA	235/55R17 99V	RA23	690	235	8.7

OBS : -O/D (Overall Diameter) -S/W (Section Width) -O.S.D (Original Skid Depth)




HANKOOK TIRES  
FITTED ON  
FORD(EU) CARS.



# OPEL



HANKOOK TIRES  
FITTED ON  
OPEL CARS.


Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
 ASTRA		215/50R17 91V	K115	650	226	7.8



# LAND ROVER



HANKOOK TIRES  
FITTED ON  
LAND ROVER CARS.








Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
 FREELANDER 2		225/65R17 102H	RH03	580	193	8.6



# HYUNDAI



**HANKOOK TIRES  
FITTED ON  
HYUNDAI CARS.**

Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
 i10		155/70R13 75T 4PR	K425	548	149	7.3
		165/60R14 75H 4PR	K425	554	168	7.3
 i20		175/70R14 84T	K715	602	175	7.8
		185/60R15 84H	K415	601	188	7.8
		195/50R16 84H	K415	602	194	7.8
 i30		185/65R15 88H	K415	618	186	7.8
		195/65R15 91H	K415	636	196	7.8
		205/55R16 91H	K415	633	206	7.8
		225/45R17 91V	K415	635	215	7.8
		T125/80D15 95M	S400	590	133	3.3
 i40		205/60R16 92V	K425	653	219	7.8
		215/50R17 95V	K115	648	231	7.8
		225/45R18 95V XL	K115	656	231	7.8
 ACCENT		175/70R14 84T	K715	602	175	7.8
		195/50/R16 84H	K415	602	194	7.8
		185/65/R15 88H	K415	619	188	7.8
		T115/70/D15 90M	S400	543	118	8.2
 AVANTE		195/65R15 91H	K425	635	201	7.8
		205/55R16 91H	K425	633	214	7.8
		215/45R17 87H	K115	630	213	7.8
 VELOSTER		215/40R18 85V	K115	629	218	3.8

OBS : -O/D (Overall Diameter) -S/W (Section Width) -O.S.D (Original Skid Depth)














# HYUNDAI



**HANKOOK TIRES  
FITTED ON  
HYUNDAI CARS.**

Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
 <b>NEW SONATA(YF)</b>		215/55R17 94V	<b>K415</b>	666	220	7.8
		T125/80D16 97M	<b>S400</b>	617	134	3.3
 <b>GRANDEUR HG</b>		245/45R18 96V	<b>K115</b>	680	238	7.8
		T125/80D16 97M	<b>S400</b>	606	126	3.0
 <b>NEW EQUUS</b>		235/55R17 99V	<b>K415</b>	690	240	7.8
		245/50R18 100V	<b>K415</b>	702	245	8.0
 <b>GENESIS</b>		225/55R17 97V	<b>K415</b>	684	225	7.8
		235/50R18 97V	<b>K415</b>	689	243	7.8
		T135/90D17 103M	<b>S400</b>	674	135	3.7
 <b>GENESIS COUPE</b>		T135/80R18 104M	<b>S300</b>	671	138	3.5
		T135/90D17 103M	<b>S400</b>	674	135	3.7
 <b>VERACRUZ</b>		245/60R18 105H	<b>RA23</b>	747	246	8.5
		245/65R17 107H	<b>RA23</b>	748	246	8.5
 <b>IX35 (TUCSON)</b>		225/60R17 99H	<b>K415</b>	701	225	8.0
		225/55R18 98H	<b>K415</b>	701	225	8.0
 <b>H-1</b> (i800, iLoad, H300)		215/70R16 108/106T 6PR	<b>RA08</b>	702	221	9.2
 <b>H100</b>	FRONT	195/70R15 100/98R 6PR	<b>RA08</b>	655	201	9.2
		195/70R15 104/102R 8PR	<b>RA08</b>	655	201	9.2
	REAR	155R12 88/86R 8PR	<b>RA08</b>	556	151	8.5

OBS : -O/D (Overall Diameter) -S/W (Section Width) -O.S.D (Original Skid Depth)











# KIA



**HANKOOK TIRES  
FITTED ON  
KIA CARS.**







Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
 <b>PICANTO</b>		155/70R13 75T	<b>K425</b>	549	151	7.1
		165/60R14 75H	<b>K425</b>	556	168	7.1
		175/50R15 75H	<b>K425</b>	559	177	7.3
 <b>SOUL</b>		195/65R15 91T	<b>K415</b>	635	202	7.8
		205/55R16 91H	<b>K415</b>	634	213	7.8
		225/45R18 91V	<b>K415</b>	656	219	7.9
		T125/80R15 95M	<b>S400</b>	590	133	3.3
		T125/80R16 97M	<b>S400</b>	606	126	3.0
 <b>RIO</b>		175/70R14 84T	<b>K702</b>	602	174	7.8
		185/65R14 86H	<b>K406</b>	594	188	7.9
		195/55R15 85V	<b>K406</b>	594	192	7.9
		205/45R16 83V	<b>K415</b>	593	199	7.8
		T125/80D15 95M	<b>S400</b>	590	133	3.3
 <b>FORTE</b>		195/65R15 91H	<b>K415</b>	635	196	7.8
		205/55R16 91H	<b>K415</b>	633	208	7.8
		T125/80R15 95M	<b>S400</b>	590	133	3.3
		T125/80R16 97M	<b>S400</b>	606	126	3.0
 <b>K7</b>		215/65R16 98V	<b>K415</b>	682	220	7.8
		225/55R17 97V	<b>K415</b>	681	231	7.8
		T125/80D16 97M	<b>S400</b>	606	126	3.0
 <b>CARENS</b>		205/65R15 94H	<b>K415</b>	644	208	8.0
		205/60R16 92H	<b>K415</b>	650	213	7.7
		T125/80D16 97M	<b>S400</b>	606	126	3.0

OBS : -O/D (Overall Diameter) -S/W (Section Width) -O.S.D (Original Skid Depth)



# KIA



Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
 <b>CARNIVAL</b> (SEDONA)		225/70R16 102H	<b>K406</b>	720	232	8.7
		235/60R17 102H	<b>K406</b>	714	231	8.6
		T135/90R17 104M	<b>S300</b>	680	141	3.5
 <b>SPORTAGE R</b>		235/55R18 100H	<b>K415</b>	711	237	8.2
		225/60R17 99H	<b>K415</b>	701	225	8.0
 <b>MOHAVE</b>		225/60R17 99H	<b>RA07</b>	776	264	8.4
		245/70R17 110H	<b>RA07</b>	776	251	8.4
		T175/90R17 119M	<b>S300</b>	762	173	3.5
 <b>K2900</b>	Front	195R15 106/104R 8PR	<b>RA08</b>	693	196	10.0
	Rear	500R12 83/82P 8PR	<b>Z30</b>	570	141	9.7
		145R13 88/86R 8PR	<b>RA08</b>	567	144	8.7
 <b>K2700</b>	Front	195R14 106/104P 8PR	<b>819</b>	668	198	10.0
		195R14 102/100R 6PR	<b>RA08</b>	670	189	8.5
	Rear	145R13 88/86R 8PR	<b>RA08</b>	567	144	8.7
 <b>K2500</b>	Front	195R14 102/100R 6PR	<b>RA08</b>	670	189	8.5
	Rear	145R13 88/86R 8PR	<b>RA08</b>	567	144	8.7

OBS : -O/D (Overall Diameter) -S/W (Section Width) -O.S.D (Original Skid Depth)



**HANKOOK TIRES  
FITTED ON  
KIA CARS.**

# CHEVROLET (GMDAT)



**HANKOOK TIRES  
FITTED ON  
CHEVROLET(GMDAT)  
CARS.**

Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
	SPARK (MATIZ)	145/70R13 71T	K702	532	147	6.5
		155/70R14 77T	K715	574	160	7.4
	AVEO (KALOS / GENTRA)	155/80R13 79T	K702	576	159	7.8
		185/55R15 82V	K406	585	194	8.1
	AVEO	185/75R14 89H	K715	634	189	7.8
	LACETTI PREMIERE	205/65R15 94V	K415	641	214	7.7
		205/60R16 92V	K415	641	214	7.7
	LACETTI	185/65R14 86H	K406	594	191	7.9
		195/55R15 85V	K406	592	199	8.1
	EPICA (TOSCA)	205/65R15 94H	K406	643	209	7.9
		205/60R16 92V	K415	649	207	8.0
	CAPTIVA (WINSTON)	215/70R16 100T	RA23	706	218	8.5
		235/60R17 102H	RA23	706	218	8.5
		235/65R17 104H	RA23	738	240	8.5
		235/50R19 99H	K415	715	245	8.0
	DAMAS/ LABO	155R12 83/81P 6PR	819	554	157	7.9
		155R12 83/81P 6PR	RA08	546	150	8.5

OBS : -O/D (Overall Diameter) -S/W (Section Width) -O.S.D (Original Skid Depth)





# SSANGYONG







HANKOOK TIRES  
FITTED ON  
SSANGYONG CARS.



# RENAULT/ SAMSUNG



HANKOOK TIRES  
FITTED ON  
RENAULT/SAMSUNG CARS.

Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
 ACTYON, REXTON		255/60R18 108H	K406	767	260	8.6
		255/70R16 111H	RA23	764	258	8.2
 KYRON		225/75R16 104H	RA23	744	223	9.2
		235/75R16 108H	RA23	758	243	8.6
		T175/90R16 117M	S300	721	186	3.5
 RODIUS		215/65R16 102T XL	RA23	688	221	8.6
		225/65R16 109/107T	RA23	702	228	8.4
 CHAIR MAN		215/55R17 94V	K105	667	238	8.0



Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
 NEW SM3 (NISSAN Almera)		205/65R15 94H	K415	642	212	8.2
		205/60R16 92H	K415	647	220	8.2
 KOLEOS (QM5)		T155/80R17 100M	S300	684	150	3.5




OBS : -O/D (Overall Diameter) -S/W (Section Width) -O.S.D (Original Skid Depth)

# MITSUBISHI



HANKOOK TIRES  
FITTED ON  
MITSUBISHI CARS.

Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
	COLT	T115/70D15 90M	S400	543	118	3.2



# MINI



HANKOOK TIRES  
FITTED ON  
MINI CARS.

Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
	MINI	195/55R16 87H 4PR	K115	616	213	8.5
		195/55R16 87V 4PR	K115	616	213	8.5



OBS : -O/D (Overall Diameter) -S/W (Section Width) -O.S.D (Original Skid Depth)



# DAIHATSU



**HANKOOK TIRES  
FITTED ON  
DAIHATSU CARS.**


Car Model	Model Type	Tire Size	Tire Pattern	O.D (mm)	S.W (mm)	O.S.D (mm)
	MOVE TANTO	155/65R14 75S	K708	552	161	6.3
	MOVE SUCCESSOR	155/65R14 75S	K708	552	161	6.1

OBS : -O/D (Overall Diameter) -S/W (Section Width) -O.S.D (Original Skid Depth)





# HANKOOK OFFICE NETWORK - EUROPE



○ Subsidiary ● Branch Office ★ Technical Center

## HANKOOK TIRE EUROPE HEADQUARTERS

Siemensstrasse 5A, 63263 Neu-Isenburg, Germany  
Tel : +49-(0)6102-8149-154 Fax : +49-(0)6102-8149-100

## Hankook Reifen Deutschland GmbH

Siemensstrasse 5A, 63263 Neu-Isenburg, Germany  
Tel : +49-(0)6102-599-82-00 Fax : +49-(0)6102-599-82-49

## Hankook Tyre U.K. Ltd.

Fawsley Drive, Heartlands Business Park,  
Daventry, Northamptonshire NN11 8UG, U.K.  
Tel : +44-(0)1327-304-100 Fax : +44-(0)1327-304-110

## Hankook France S.A.R.L.

115 Boulevard Stalingrad Central Parc 2  
69100 Villeurbanne - France  
Tel : +33-(0)4-72-69-76-40 Fax : +33-(0)4-78-94-15-72

## Hankook Tire Italia S.R.L.

Centro Direzionale Colleoni, Palazzo Liocomo 1  
Via Paracelso 2, 20041 Agrate Brianza (MB), Italy  
Tel : +39-039-684-631 Fax : +39-039-6091-372

## Hankook Espana S.A.

Parque Empresarial Natea  
Av. de la Industria No.4, Edificio 3, 2D  
28108 Alcobendas (Madrid), Spain  
Tel : 34+(0)90-210-2716 Fax : +34-(0)91-662-9802

## Hankook Tire Netherlands Sales B.V.

Beechavenue 102  
1119 PP Schiphol-Rijk, The Netherlands  
Tel : +31-(0)20-316-1710 Fax : +31-(0)20-316-1729

## Hankook Tire Europe Distribution Center

Koerilenstraat 2 - 6, 3199 LR,  
Distripark Maasvlakte Rotterdam  
The Netherlands, Portnumber: 9018  
Tel : +31-(0)181-353-010 Fax : +31-(0)181-353-013

## Hankook Tire Co., Ltd. Budapest Office

IP West Building, Budafoki ut 91-93,  
H-1117 Budapest, Hungary  
Tel : +36-1-464-3663 Fax : +36-1-464-3669

## Hankook Tire Co., Ltd. Moscow Office

3rd Floor, Building 4, Dom 2/4, Lujnetskaya Naberejnaya,  
Moscow, 119270  
Tel : +7-495-956-2340 Fax : +7-495-956-2343

## Hankook Tire Co., Ltd. Istanbul Office

Dereboyu cad. Meydan sk. Beybi Giz Plaza  
NO:1 kat:21 D:80 34398 Maslak, Istanbul, Turkey  
Tel : +90-(0)212-290-3690 Fax : +90-(0)212-290-3691

## Hankook Tire Stockholm Office

Kanalvagen 10A, 194 61 Upplands Väsby, Sweden  
Tel : +46 (0)859083900 Fax : +46 (0)859083912

# HANKOOK LIMITED WARRANTY

## ORIGINAL EQUIPMENT PASSENGER & LIGHT TRUCK TIRES INCLUDING TEMPORARY TIRES

### 1. TIRE BE WARRANTED FREE FROM DEFECTS IN MATERIALS AND WORKMANSHIP

This warrants each Hankook Tire with new vehicles are equipped against defects in materials or workmanship in normal use and service on the vehicle with which it came for the life of the original tread.

### 2. WHAT IS WARRANTED AND FOR HOW LONG

HankookTire are warranted against defects in materials or workmanship in normal use for the life of the original usable tread.

### 3. FREE REPLACEMENT

- If Hankook Radial Passenger & Light Truck Tires fail as a result of defect in material and/or workmanship within the first 25% of treadwear, the tire will be replaced with a new, comparable Hankook Tire at no charge including mounting and balancing charges.
- Hankook NON RADIAL(BIAS) LIGHT TRUCK TIRES will replace any tire covered by this warranty which fails as a result of defect in materials and workmanship during the first 10% of usable treadwear. The tire will be replaced with a new, comparable Hankook Tire. Owner pays mounting and balancing charges.

### 4. TREADWEAR PRORATED REPLACEMENT

Tires not qualifying for free replacement will be allowed a credit toward purchase of a new, comparable Hankook Tire based upon the amount of tread actually worn. The cost of mounting, balancing and any other service charges or applicable taxes should be paid by the user. Otherwise adjustment for compensation will be made on a pro-rata basis calculated by multiplying the actual current dealer selling price by the percentage of remaining usable tread depth.

### 5. WHAT IS NOT COVERED BY THE WARRANTY

- Irregular wear or tire damage due to :
  - Road hazards such as punctures, cuts, snags, scuffs, carcass bruised or impact breaks.
  - Fire, wreck or collision.
  - Improper inflation, overloading, high speed spinning, improper mounting or demounting, running flat, off-road use, racing, vandalism, willful damage or abuse.
  - Misalignment, wheel imbalance, defective brakes or shock absorber use of tire chains.
  - Any tire which has failed as a result of adding material(e.g.tire fillers, sealant, or balancing substances)
- Tires fitted to anything other than the original vehicles.
- Tire worn beyond treadwear indicator(2/32nds inch or 1.6mm tread remaining).
- Tire branded "NA"(meaning no adjustment) or "BLEM"(meaning blemished).
- Loss of time inconvenience, loss of use of the vehicle or consequential damage.
- Ride disturbance caused due to damaged wheels or after the first 1/32 inch(0.8mm) of treadwear
- Tire with weather cracking was purchased more than four years prior to presentation for adjustment.
- Flat spot tire

### 6. HANKOOK OBLIGATIONS

Replacement qualifying under this warranty will be made by a participating Hankook Dealer or a participating Car Dealer.

### 7. OWNER'S OBLIGATION

- You must present the tire to a participating Hankook Dealer or a participating Car Dealer.
- For free replacement, a proof of purchase date such as car dealer invoice should be presented.
- No claim will be recognized unless submitted on a Hankook claim form completely filled out and signed by the owner or a participating Hankook Dealer and Car Dealer.

### ▲ WARNING

All tires must be routinely inspected for damage or abnormality and removed from service or repaired as needed. All inflation pressure must be checked with a gauge and maintained at recommended levels. Failure to do the preceding or to abuse or otherwise improperly maintain your tires may result in premature deterioration, tire failure, accident and injury or death.

### ▲ PASSENGER TIRE MOUNTING WARNING

Motorists are strongly cautioned against mounting their own tires due to the safety hazards involved. This is a job for trained service personnel.

- NEVER mount tires on rims which are not smooth and clean.
- ALWAYS lubricate both beads and rim flanges with a solution made specifically for that purpose or with a vegetable oil soap and water solution only.
- NEVER use antifreeze, silicones or petroleum base lubricants to lubricate beads and rim flanges.
- NEVER inflate a tire which is lying on the floor or other flat surface. ALWAYS use a tire mounting machine with a hold down device.
- NEVER inflate to seat beads without using extension hose with gauge an clip on chuck.
- NEVER stand next to seat beads without using extension hose with gauge and clip on chuck.
- NEVER exceed 40 psi pressure.
- ALWAYS set pressure to the recommended operating pressure after beads have seated.

### □ SPEED-RATED TIRES

Speed-rated tires are identified by letters P,Q,S,T,H,V,W or Z as either part of the size designation(e.g.,HR), or part of the service description adjacent to the size designation(e.g., 94H) and indicates the maximum speed capability of the tire when properly loaded and inflated. However, even when properly loaded and inflated, driving for prolonged periods at highspeeds can cause tire damage and possible tire failure which could lead to an accident. Original equipment speed-rated tires must be replaced with tires of the same or higher speed rating if the speed capability of the vehicle is to be maintained. Consult your Hankook dealer for the tires best suited to your vehicle driving habit. Repairing of speed-rated tires must be done in accordance with RMA" repair procedures and is limited to one 1/4" diameter repair in the tread area. The speed rating of retreaded tires is assigned by the retreader as the original manufacture's rating is void.



**Hankook Tire Europe Headquarters**

Siemensstrasse 5A, 63263 Neu-Isenburg, Germany

Tel: +49-(0)6102-8149-199 Fax: +49-(0)6102-8149-100

[hankooktire-eu.com](http://hankooktire-eu.com)